

Cetol® Interior Stain

A quick drying, low odor, waterborne stain for the coloration of hard and soft woods. Cetol Interior Stain is compatible with both solvent and waterborne Sikkens Interior topcoats.

Low odor.

Quick drying.

Simple application.

Compatible with solvent and waterborne Interior topcoats.

Cetol Interior Stain is used as an interior color coat on soft and hard woods for all application areas. Cetol Interior Stain must be topcoated with a clear coat for surface protection (refer to the Sikkens Product Application Guide for details.)

Method - Nylon polyester brush or synthetic pad applicator followed by wiping with a damp lint-free rag.

Temperature - 50°F - 80°F (10°C - 27°C).

Thinning - For large surfaces dilution by 10% with water may be necessary.

Cleaning of Equipment - Clean promptly with mild soap and clean water.

Coverage - Approximately 600 sq. ft. per U.S. gallon (15 sq. m. per liter), depending on the porosity of the wood.

Drying Time - Touch dry after 30 minutes; recoatable after 2 hours for light colors and 4 hours for dark colors.

CHARACTERISTICS

USE

APPLICATION

Viscosity - 60-78 Ku @ 73°F (23° C) depending on color

Density - 1.08± - 0.05 kg/dm³

Solids by Weight - 20 - 25% depending on color

Solids by Volume - 15 - 20% depending on color

Gloss Level - Flat

Flow - Good

Adhesion - Excellent

V.O.C. - Less than 2.9 lbs./gal., 350 g/L - water-free.

(004) Natural Oak	(044) Cherry	(074) Ipswich Pine
(010) Walnut	(045) Mahogany	(078) Natural
(023) Burgundy	(061) Hunter Green	(083) Fruitwood
(030) Opal White	(072) Butternut	(085) Teak

U.S. quart & 1/2 pints
U.S. gallon (078 - Natural Only)

Shelf Life - Approximately 3 years in an unopened container.

Storage - Protect from frost. Keep from freezing.

FLASHPOINT:

Cetol Interior Stain > 212°F (100°C)

WARNINGS:

Do not take internally.
Keep out of reach of children.
Close container after use.

FIRST AID TREATMENT:

Refer to the Material Safety Data Sheet.

The technical information and suggestions for use made herein are based on Akzo Nobel Coatings Inc.'s research and experience and are believed to be reliable, but such information and suggestions do not constitute a warranty.

Since Akzo Nobel Coatings Inc. has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves by preliminary tests or otherwise, the suitability of the product for their purposes. When testing, the complete system that has been chosen must be applied.

PROPERTIES

COLOR RANGE

PACKAGING

STORAGE

HEALTH & SAFETY DATA

PRODUCT DISCLAIMER